



















- Jia Y. and T. A. Reddy. 2003. Characteristic physical parameter approach to modeling chillers suitable for fault detection, diagnosis, and evaluation. *Journal of Solar Energy Engineering* 125 (3): 258-65.
- McDonald, E., R. Zmeureanu, and D. Giguère. 2013. Virtual flow meter for chilled water loops in existing buildings. *ASHRAE Transactions*; 2014, 120(2).
- Nassif, N., S. Kajl, and R. Sabourin. 2003. Modélisation des composants d'un système CVAC existant. In *VIe Colloque Interuniversitaire Franco-Québécois, Québec, Canada*. CIFQ2003 / 12-01.
- Padilla, M., D. Choinière, and J. A. Candanedo. 2015. A model-based strategy for self-correction of sensor faults in VAV air handling units. *Science and Technology for the Built Environment*.
- Padilla M. and D. Choinière. 2015. A combined passive-active sensor fault detection and isolation approach for air handling units. *Energy and Buildings* 99: 214-9.
- Roth K., D. Westphalen, and J. Brodrick. 2008. Ongoing commissioning. *ASHRAE Journal* 50 (3): 66.
- Song, L., I. Joo, & G. Wang. 2012. Uncertainty analysis of a virtual water flow measurement in building energy consumption monitoring. *HVAC&R Research*, 15:5, 997-1010.
- Zibin N. 2014. *A bottom-up method to calibrate building energy models using building automation system (BAS) trend data*. Msc Degree., Concordia University.